



30° AUTOCENTRANTI IN ANGOLARE - 30° ANGLE BAR SELF-CENTRING ELEMENTS

| CODICE CODE | H | HI | A | B | E | L | D MAX | P | PESO KG WEIGHT KG | NASTRO BELT |
|-------------|-----|------|------|------|------|------|-------|-----|-------------------|-------------|
| STAC03065 | 270 | 133 | 950 | 890 | 715 | 258 | 108 | 130 | 23,560 | 650 |
| STAC03080 | 309 | 140 | 1150 | 1090 | 892 | 323 | | | 27,330 | 800 |
| STAC03100 | 341 | | 1350 | 1290 | 1070 | 388 | | | 31,590 | 1000 |
| STAC03120 | 384 | | 1600 | 1540 | 1300 | 473 | | | 35,620 | 1200 |
| STAC03140 | 430 | | 154 | 1800 | 1740 | 1480 | | | 538 | 46,720 |
| STAC03160 | 466 | 2000 | 1940 | 1672 | 608 | 608 | | | 57,820 | 1600 |
| STAC13080 | 329 | 160 | 1150 | 1090 | 892 | 323 | 133 | 130 | 28,080 | 800 |
| STAC13100 | 361 | | 1350 | 1290 | 1070 | 388 | | | 32,340 | 1000 |
| STAC13120 | 404 | | 1600 | 1540 | 1300 | 473 | | | 36,370 | 1200 |
| STAC13140 | 450 | 174 | 1800 | 1740 | 1480 | 538 | | | 47,470 | 1400 |
| STAC13160 | 486 | 2000 | 1940 | 1670 | 608 | 608 | | | 58,570 | 1600 |

DESCRIZIONE PRODOTTO

Le stazioni di andata autocentranti servono a contenere lo spostamento del nastro.

Vengono montate ad una distanza variabile tra i 12 e i 25 metri. Sono costituite da due traverse, una fissa ancorata al telaio del nastro e una mobile montata su una ralla a sfere che permette una rotazione di 5° circa.

PRODUCT DESCRIPTION

Self-centring troughing triple set are for limiting the displacement of the belt. They are mounted at distances that range from 12 to 25 metres. They are composed of two cross-members, a fixed one anchored to the belt frame and a mobile one mounted on a ball-bearing fifth wheel that permits rotation of about 5°.